

TARUS BLUE VAPOR BARRIER

DECLARATION OF PERFORMANCE




DODAVATEL PRO DŘEVOSTAVBY A STŘEŠNÍ KONSTRUKCE

1. Unique identification code of the product type:

 +420 778 585 325 obchod@tarus.cz www.tarus.cz	 +420 778 585 325 obchod@tarus.cz www.tarus.cz	 +420 778 585 325 obchod@tarus.cz www.tarus.cz	 +420 778 585 325 obchod@tarus.cz www.tarus.cz
Parozábrana TARUS BLUE 200	Parozábrana TARUS BLUE 200	Parozábrana TARUS BLUE 200	Parozábrana TARUS BLUE 200
Délka role: 50 m Šířka role: 3 m Plocha: 150 m ²	Délka role: 50 m Šířka role: 3,2 m Plocha: 160 m ²	Délka role: 40 m Šířka role: 3,5 m Plocha: 140 m ²	Délka role: 25 m Šířka role: 4 m Plocha: 100 m ²

2. Intended use or uses of the construction product, in accordance with the relevant harmonised technical specification, as foreseen by the distributor:

PE - vapor barrier



3. Manufacturer



DODAVATEL PRO DŘEVOSTAVBY A STŘEŠNÍ KONSTRUKCE

Pavelkova 1210/10B, 779 00 Olomouc

4. Authorized representative

not specified

5. INVITATION system

assessment system 3

6a. Harmonized standard

EN 13984:2013

Notified body(ies)

1213

6b. European Assessment Document

does not apply

MORE INFORMATION:



TARUS business services sro

Pavelkova 1210/10B

779 00 Olomouc

Email: obchod@tarus.cz

Website: www.tarus.cz



TARUS BLUE VAPOR BARRIER

DECLARATION OF PERFORMANCE



7. Features

FEATURES	UNIT	VALUE	TOLERANCE		TECH SPECS.
Weight per unit area	g/m ²	188	-5%	5%	EN 1849-2
Length	m	50	-3%	3%	EN 1849-2
Width	m	3; 3.2; 3.5; 4	-1%	1%	EN 1849-2
Thickness	mm	0.2	-5%	5%	EN 1849-2
Reaction to fire	(class)	E	-	-	EN 13501, 11925-2
Waterproof	(class)	W1			EN 1928
Vapor permeability (equivalent diffusion thickness Sd)	(m)	>140			EN 1931
Tensile strength in longitudinal/transverse direction	(N/50mm)	>160 / >140			EN 13859-1, 12311-2
Resistance to further tearing	(N)	>100 / >100			EN 13859-1, 12310-1
Effect of artificial aging on water vapor permeability		suits			EN 1296, 1931
Hazardous substances		*npd			

*npd - no indicator determined

8. Relevant technical documentation and/or specific documentation

not issued

The properties of the above product are in accordance with the set of declared properties and test report No. 72185/06-X.
This declaration of performance is issued under the sole responsibility of the manufacturer identified above, in accordance with Regulation (EU) No 305/2011.

Signed for and on behalf of the manufacturer:



ROBERT TATAI Managing Director

TARUS business services sro
In Olomouc on 1 January 2026

MORE INFORMATION:



TARUS business services sro
Pavelkova 1210/10B
779 00 Olomouc

Email: obchod@tarus.cz
Website: www.tarus.cz