

TARUS TAPE ROOF GREY/WHITE®

SEALING TAPE FOR SEALING NAIL JOINTS



- suitable for waterproof sealing of nail and screw holes
- meets the requirements of the ZVDH directive
- for indoor and outdoor use



Use of TARUS TAPE ROOF GREY WHITE®

TARUS TAPE ROOF® is a single-sided adhesive sealing tape for waterproof sealing of nail and screw holes in underlayment membranes and roof protective films.

- High adhesion to membranes, wood and building materials.
- Nail sealing is necessary for roofing, especially on low slopes. Nail sealing tape protects against water penetration and therefore meets the requirements ZVDH guidelines.
- Resistance to heavy rain up to 600 pascals.

EXAMPLES OF USE:

When attaching the securing battens to the rafters, nails or screws will penetrate the underlayment membrane or roof protection film. Water can enter through these holes and cause structural damage.

For sealing areas after application of nails and staples in vapour barriers and vapour brakes.

APPLICATION:

Apply TARUS TAPE ROOF nail sealing tape either to the bottom of the securing battens or to the underlying membrane parallel to the rafter. Then it is necessary to fasten the roof batten to the rafter using HECO, REISSER, SIHGA screws, which will compress the nail sealing tape. The surface must be dry and free of grease, sawdust and dust before application.



TOP product, 10-year system warranty
TÜV SÜD certification



• Airtightness



• Extreme stickiness



• High pressure resistance up to 600 pascals



• Suitable for low roof slopes

Recommended products:

- TARUS BUTYL PRIMER®
- TAJIMA cutting knife
- TAJIMA cutting shears
- TAJIMA tape measure



Made in Germany.
Importer: TARUS commercial services sro | Nedvzdova 389/2,
Povel, 779 00 Olomouc, Czech Republic. www.tarus.cz

FEATURES	
Packaging	1/1 pc
Auxiliary material	PE - polyethylene
Glue base	synthetic rubber
Color	Anthracite / White
Total thickness	3mm
Width	60mm
Length	30 m
Min. processing temperature	5°C
Min./max. temperature resistance	-30 to 80°C
UV resistance	3 months, when exposed to weather
Shelf life from date of manufacture	24 months

MORE INFORMATION:



TARUS business services sro
Nedvzdova 389/2
779 00 Olomouc

Phone: +420 601 505 323
Email: obchod@tarus.cz
Website: www.tarus.cz

