

TARUS TAPE TOP^{NANO}®

ADHESIVE AND SEALING TAPE

- exceptionally sticky universal adhesive tape
- suitable for creating airtight and waterproof joints
- for indoor and outdoor use
- equipped with nano technology



TOP product, 10-year system warranty
TÜV SÜD certification



• Airtightness Sd 30



• Extreme stickiness

Recommended products:

- TARUS BUTYL PRIMER®
- TAJIMA cutting knife
- TAJIMA cutting shears
- TAJIMA tape measure



Made in Germany.
Importer: TARUS obchodní služby sro | Pavelkova 1210/10B,
779 00 Olomouc, Czech Republic. www.tarus.cz



DODAVATEL PRO DŘEVOSTAVBY A STŘEŠNÍ KONSTRUKCE

Using TARUS TAPE TOP^{NANO}®

TARUS TAPE TOP^{NANO}® is ideal for bonding vapour barriers, vapour barriers and roof protection foils and has been tested for use with these foils. We recommend using these foils for optimal results when using an airtight system.

- UV resistance: 3 months.
- Equipped with nano technology. Increased adhesion and compatible with TARUS NANO 120 vapor barriers, the entire range of TARUS BLUE vapor barriers and vapor brakes. my TARUS VAPOR 20
- Maximum reliability in building breathability tests.
- Protects against moisture and mold growth.
- For permanent bonding of roof protective foils, vapor barriers and TARUS® vapor barriers.
- For bonding overlapping parts of these films or joints and openings.
- Airtight bonding of OSB board joints.
- TARUS TAPE TOP NANO® is characterized by fast, easy and safe applications.
- Adheres to most standard construction surfaces, also suitable for outdoor use.
- It has a carrier layer made of flexible material and easily adheres to punctures.
- Does not contain solvents.

Attach TARUS TAPE TOP NANO® to the overlap joint by removing the release paper.

Gradually remove the remaining release paper and apply the pressure-sensitive adhesive tape along the entire length of the overlap joint. Make sure that sufficient contact pressure is applied.

After sticking, cut the tape with a knife. Do not expose the stuck tape to prolonged stress.

TARUS TAPE tapes meet water vapor transmission (Sd) according to EN ISO 12572.

MORE INFORMATION:



TARUS business services sro

Pavelkova 1210/10B

779 00 Olomouc

Email: obchod@tarus.cz

Website: www.tarus.cz



TECHNICAL DATA SHEET

TARUS TAPE TOP[®] NANO

ADHESIVE AND SEALING TAPE

- exceptionally sticky universal adhesive tape
- suitable for creating airtight and waterproof joints
- for indoor and outdoor use
- equipped with nanotechnology



FEATURES	
Packaging	1/10 pcs
Auxiliary material	LDPE film with mesh fabric
Glue base	Acrylic dispersion
Color	White with print
Width	60mm
Length	25 m
Min./max. processing temperature	5 to 50°C
Min./max. temperature resistance	-40 to 100°C
UV resistance	3 months
Contains solvents	NO
Weight	180 g/m ²
Covering material	silicone paper
Adhesion	DIN EN 1939 approx. 35N/25 mm
Force	0.28 mm (without liner paper)



TOP product, 10-year system warranty

TÜV SÜD certification



• Airtightness Sd 30



• Extreme stickiness



Made in Germany.
 Importer: TARUS obchodní služby sro | Pavelkova 1210/10B,
 779 00 Olomouc, Czech Republic. www.tarus.cz

MORE INFORMATION:



TARUS business services sro

Pavelkova 1210/10B

779 00 Olomouc

Email: obchod@tarus.czWebsite: www.tarus.cz