

TARUS TAPE ROOF®

SINGLE-SIDED ADHESIVE TAPE FOR DIFFUSION FILM



- adhesive tape for diffusion foils with extreme adhesive strength
- ensures high-quality joints of diffusion foils
- high adhesion to non-woven materials, PES, etc.
- highly resistant to aging
- suitable for gluing over diffusion foil joints or minor repairs in case of damage
- for indoor and outdoor use



Use of TARUS TAPE DACH®

TARUS TAPE DACH® is a single-sided adhesive tape for covering the overlap of safety diffusion foils or for minor repairs in case of their damage. It is also suitable for sealing round or square penetrations (e.g. pipes, antenna masts, etc.) through the diffusion foil. Thanks to its excellent adhesion, it serves for a perfect connection of the diffusion foil to wooden, brick and concrete substrates.

It is mainly used for permanent, breathable bonding of diffusion membranes against water seeping into the subroofing resulting from melting blown-in powder snow.

It stands out especially for its excellent adhesion to non-woven fabrics, PES, etc., thus guaranteeing a high-quality glued joint. **TARUS TAPE DACH®** is very resistant to moisture and diffusion-open. It is also used when it is necessary to create a tightness class of DHV 4, DHV 3 and DHV 2 in the roof sheathing.

APPLICATION:

TARUS TAPE DACH® is a self-adhesive tape consisting of a special non-slip fleece in wet environments and a single-sided highly adhesive polyacrylate adhesive covered with a protective strip. It is pressure-sensitive, has extremely high initial and permanent adhesion, good shear strength and heat resistance.

When installing **TARUS TAPE DACH®**, the substrate must be dry, free of dirt, dust, grease and oil. Porous and coarse substrates, such as masonry, concrete or plaster, must be sufficiently treated with a suitable primer before gluing.

TARUS TAPE DACH® is not suitable for bonding joints with mechanical stress, therefore apply the adhesive tape so that it is not stretched and press it carefully. Press the tape properly and smooth it against the surface.



TOP product, 15-year system warranty
TÜV SÜD certification



• UV stability 4 months



• Extreme stickiness

Recommended products:

- TARUS BUTYL PRIMER®
- TAJIMA cutting knife
- TAJIMA cutting shears
- TAJIMA tape measure



Made in Germany.
Importer: TARUS commercial services sro | Nedvřdova 389/2,
Povel, 779 00 Olomouc, Czech Republic. www.tarus.cz

FEATURES	
Packaging	1/12 pcs
Auxiliary material	PP spunbound with PP coating
Glue base	Polyacrylic
Color	Anthracite
Width	50mm
Length	25 m
Min./max. processing temperature	5 to 40°C
Min./max. temperature resistance	-30 to 80°C
UV resistance	3 months
Contains solvents	NO
Breaking strength	γ70N/25mm
Elongation at break	50-100%
Adhesion	DIN EN 1939 approx. 30N
Force	0.62 mm (without liner paper)

MORE INFORMATION:



TARUS business services sro
Nedvřdova 389/2
779 00 Olomouc

Phone: +420 601 505 323
Email: obchod@tarus.cz
Website: www.tarus.cz

